

## Front/ Rear View


Front



Rear



## Outward Appearance



## Functions by Screen



WATCH SCREEN

PTZ SCREEN

SEARCH SCREEN

## Application

Some recommended installation areas are Security Companies, Change Booths, Casinos, Pawnshops, Jewelers, Galleries, Exhibition Halls, Department Stores, Convenience Stores, Discount Offices, Hospital, Police Stations, Subway Stations, Airports, Banks etc.

## Features

- High Quality Realtime Display – Max. 120fps(NTSC) 100fps(PAL)
- High Quality and High Speed Recording – Max. 120fps(NTSC) 100(PAL)
- Various Resolutions on Display and Recording – 640×480, 320×240, 160×120(NTSC), 768×576, 384×288, 192×144(PAL)
- Modified MPEG4
- 1, 4, 6, 9, 16 Division
- Watchdog Feature
- Kodicom, Pelco, Dennyard, Bosch, Samsung and many more PTZ protocol included
- Watermark Function
- Remote Observation Through Network
- Emergency Screen Auto Transfer to Center Software
- User friendly Graphic User Interface

## Specifications

Model		DN-4516
Display	Speed	NTSC : 120fps PAL : 100fps
	Screen Division	1, 4, 6, 9, 13, 16 Division
Recording	Max. Speed (@ CIF)	NTSC : 120fps PAL : 100fps
	Resolution	NTSC : 640×480, 320×240, 160×120 PAL : 768×576, 384×288, 192×144
	Recording Option	Continuous, Motion, Sensor and Pre-Alarm
Video	Format	NTSC/PAL
	CODEC	Modified MPEG4
	Input	16ch
	Output	VGA, Programmable spot out (2ch full)
System	OS	MS WINDOWS 2000
Audio	Input	1ch (MIC input)
	Output	1ch
	CODEC	G. 726 (8KHz Mono)
Alarm	Input	8 Ports
	Output	8 Ports
Network	Transmission	LAN/PSTN/ISDN/XDSL/Leased Circuit
	Protocol	TCP/IP (support dynamic IP)
Backup	Device	USB, CD-RW (optional), Network, DVD-RW (optional)
Other Function	Remote Control	Remote Software (CMS)
	Remote Alarm	E-mail, CMS report
	PTZ	RS232C/485
	W/D Function	Yes
	Image Authentication	Watermark
	Language	17 Languages
	Password	Multi-Level User Password Authorization
	USB	6 Port (USB 2.0)
	Working Temperature	0°C ~ +50°C
	Power Source	AC 100 ~ 240V, 50/60Hz
Dimensions	430mm(W) × 176mm(H) × 460mm(D)	
Weight(net)	18Kg (39.6lbs)	

※ Specifications subject to change without notice.