

## RH-704HV all-real-time DVR

- The third generation DVR
- Real time Recording & Display
- Embedded DAVINCI CPU
- H.264 video compression
- Support USD 2.0



### Specifications

Mode Number	RH-704HV		
Main Processor	High performance embedded DAVINCI microprocessor		
Operating System	Embedded Linux		
Video Compression	H.264		
Video Format	MPEG 4		
Video Resolution	Format	PAL	NTSC
	D1(4 CIF)	704 x 576	704x 480
	CIF	352 x 288	352 x 240
Video Input	4		
Video Input Interface	BNC (Electrical Level: 1.0Vp-p, resistance: 75Ω)		
Video output	1 channel, BNC (Electrical Level: 1.0Vp-p, resistance: 75Ω)		
Video loop out	--		
Total frame rate (PAL/NTSC)	PAL: 100fps	NTSC: 120fps	
Stream type	Video / Video & Audio		
Bandwidth Control	32Kbps--2Mbps, self-define		
Audio Input	1		
Audio Output	1 channel, RCA (Linear Electrical Level, Resistance: 600Ω)		
Communication Port	1 RJ45 10M/100M Self-adaptive Ethernet Interface, 1 RS232 interface, 1 RS485 interface		
Hard Disk Interface	1 IDE interface, can support IDE HDD and each HDD can support 2000GB		
VGA Interface	1 VGA interface, support resolution: 800×600/60Hz, 800×600/75Hz, 1024×768/60Hz		
External Alarm In	4		
Relay Output	1		
Power Supply	DC 12V		
Power Consumption	<=10W		
Temperature	-10℃--+55℃		
Humidity	10%--90%		
Dimension	315mm (W) x 230mm (D) x 45mm (H)		
Weight	2.8Kg (Hard Disk is not included)		

### 7Suns Technologies

Room 1102. Grand Business Plaza, 153 Wai Yip St.,  
Kwun Tong, Kowloon, Hong Kong